

FILTERS



Thermax offers a wide range of filtration systems standardised on the basis of specific velocities for each type of filter. Filters are available with single 5-way valve operation & multiple valve operation depending on the flow rate & the application. Filters are available in MS (painted), FRP & HDPE construction.

TYPES OF FILTERS:

- **Dual media (DUAL MEDIA FILTERS ARE DESIGN TO HANDLE INLET WATER TURBIDITY UPTO 100PPM WITH PROPER ALUM DOSING/_POLYELECTROLYTE DOSING.)**
- **Activated Carbon**
- **Iron removal**
- **Garnet**
- **Pressure sand**

All standard filters are painted internally with anti-corrosive paint & externally with two coats of enamel paint. Semi-automatic versions of the filters are also available.

MODELS & CAPACITIES:

VERSA	FLOW RANGE (m3/hr)
DMF	10-200
ACF	10-200
IRF	7.5-200
GF	10-100

FXL	FLOW RANGE (m3/hr)
DMF	0.3-13
ACF	0.3-12
IRF	0.3-12
GF	0.3-12
PSF	0.3-10

EZ	FLOW RANGE (m3/hr)
DMF	0.3-13
ACF	0.3-12
IRF	0.3-12
GF	0.3-12
PSF	0.3-10